

## SDR Wideband Multi Mode RF Transceiver

Part Number	Channels	Data width (Bit)	Frequency (MHz)	Rx Image Rejection (dBc)	NF (dB)	Tx spurious suppression	Channel Isolation (dB)	Hopping Speed (hops/s)	Bandwidth (MHz)	DPD Support	Max Dissipation (W/CH)	Compatible PN	Grade	Package
<b>HY9261</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	I	Plastic FCBGA 15mm×15mm
<b>HY9261N</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	N1	Plastic FCBGA 15mm×15mm
<b>HY9261H</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	B	Ceramic BGA 15mm×15mm
<b>HY9261S</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	I	Plastic FCBGA 15mm×15mm
<b>HY9261SN</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	N1	Plastic FCBGA 15mm×15mm
<b>HY9261SH</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	NO	0.8	AD9361	B	Plastic FCBGA 15mm×15mm
<b>HY9261A</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	YES	0.8	ADRV9002	I	Plastic FCBGA 15mm×15mm
<b>HY9261AN</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	YES	0.8	ADRV9002	N1	Plastic FCBGA 15mm×15mm
<b>HY9261AH</b>	3Rx/2Tx	16	70-2700	50	≤4	50	70	4000	0.02-60	YES	0.8	ADRV9002	B	Ceramic BGA 15mm×15mm