

Part Number	Cap (μ F)	Max Voltage (kV)	Energy (kJ)	Voltage Rev %	Peak Current (kA)	Design Life	Approx. Inductance (nH)	Case Dimensions H x W x L	Approx Weight
33838	120.00	10	6	80	100	1 X 10 ⁵	35	8.0 x 14.0 x 24.1 in. (204 x 356 x 613 mm)	165 lbs (74.8 kgs)
33715	200.00	10	10	10	100	2 X 10 ⁵	35	7.25 x 14 x 24.1 in. (185 x 356 x 613 mm)	145 lbs (65.8 kgs)
32259	500.00	10	25	10	100	4 X 10 ⁴	40	11 x 14 x 26.5 in. (280 x 356 x 674 mm)	250 lbs (113.4 kgs)
33940	430.00	11	26	10	125	3 X 10 ³	35	7.25 x 14 x 27.3 in. (185 x 356 x 694 mm)	170 lbs (77.1 kgs)
33943	525.00	11	31.5	10	125	3 X 10 ³	35	8.38 x 14 x 27.3 in. (213 x 356 x 694 mm)	200 lbs (90.7 kgs)
32312	680.00	11	41	10	125	3 X 10 ³	35	11.0 x 14.0 x 27.5 in. (280 x 356 x 699 mm)	260 lbs (117.9 kgs)
32327	830.00	11	50	10	150	3 X 10 ³	40	12.0 x 16.0 x 27.5 in. (305 x 407 x 699 mm)	320 lbs (145.2 kgs)
33464	30.00	20	6	80	50	1 X 10 ⁵	45	8.38 x 14 x 24.1 in. (213 x 356 x 613 mm)	165 lbs (74.8 kgs)
33593	50.00	20	10	10	50	2 X 10 ⁵	60	7.25 x 14.0 x 24.6 in. (185 x 356 x 625 mm)	145 lbs (65.8 kgs)
33677	52.00	22	12.5	10	65	1 X 10 ⁵	60	8.38 x 14.0 x 27.0 in. (213 x 356 x 686 mm)	185 lbs (83.9 kgs)

32235	125.00	20	25	10	50	4×10^4	50	11.0 x 14.0 x 26.5 in. (280 x 356 x 674 mm)	250 lbs (113.4 kgs)
33941	107.00	22	26	10	100	3×10^3	50	7.25 x 14.0 x 27.3 in. (185 x 356 x 694 mm)	170 lbs (77.1 kgs)
33944	130.00	22	31.5	10	100	3×10^3	50	8.38 x 14.0 x 27.3 in. (213 x 356 x 694 mm)	200 lbs (90.7 kgs)
32313	170.00	22	41	10	125	3×10^3	50	11.0 x 14.0 x 27.5 in. (280 x 356 x 699 mm)	260 lbs (117.9 kgs)
32349	206.00	22	50	10	150	3×10^3	45	12.0 x 16.0 x 27.4 in. (305 x 407 x 696 mm)	320 lbs (145.2 kgs)
32276	12.50	40	10	60	180	2.5×10^4	40	11.0 x 14.0 x 27.0 in. (280 x 356 x 686 mm)	265 lbs (120.2 kgs)
32169	32.00	40	25	10	50	4×10^4	75	11.0 x 14.0 x 27.0 in. (280 x 356 x 686 mm)	255 lbs (115.7 kgs)
33942	27.00	44	26	10	100	3×10^3	80	7.25 x 14.0 x 27.6 in. (185 x 356 x 701 mm)	170 lbs (77.1 kgs)
33945	32.00	44	31.5	10	100	3×10^3	80	8.38 x 14.0 x 27.6 in. (213 x 356 x 701 mm)	200 lbs (90.7 kgs)
32314	42.00	44	41	10	150	3×10^3	70	11.0 x 14.0 x 27.6 in. (280 x 356 x 701 mm)	260 lbs (117.9 kgs)

32283	52.00	44	50	10	150	3×10^3	70	12.0 x 16.0 x 27.6 in. (305 x 407 x 701 mm)	325 lbs (147.5 kgs)
32184	6.00	60*	10.8	60	250	1×10^4	40	11.0 x 14.0 x 27.0 in. (280 x 356 x 686 mm)	265 lbs (120.2 kgs)
32389	8.40	60*	15	40	200	1×10^4	40	11.0 x 14.0 x 28.0 in. (280 x 356 x 711 mm)	275 lbs (124.7 kgs)
32170	11.00	60	20	10	50	5×10^4	100	11.0 x 14.0 x 27.0 in. (280 x 356 x 686 mm)	255 lbs (115.7 kgs)
32116	1.30	100**	6.5	30	150	3.5×10^4	40	11.0 x 14.0 x 25.0 in. (280 x 356 x 635 mm)	230 lbs (104.3 kgs)
32424	3.00	100**	15	20	260	1×10^4	40	11.0 x 14.0 x 25.0 in. (280 x 356 x 635 mm)	235 lbs (106.6 kgs)

Modified Scyllac - up to 45 kV in lab air at sea level, up to 60 kV under oil.

**Full Scyllac - up to 60 kV in lab air at sea level, up to 100 kV under oil.